

Recognition Systems

HandPunch® 3000

Biometric Time & Attendance Terminal

Put your hands on the accurate, affordable solution.

Ingersoll Rand Recognition Systems now brings the accuracy and convenience of biometric technology easily within reach of any time and attendance applications. In operations that range from coal mines to clean rooms, Ingersoll Rand Recognition Systems have proven themselves to be a practical and precise solution. Our terminals are so affordable, it doesn't make sense to consider any other technology.

Smarter than card-based terminals

There are no cards to create, administer, carry – or lose. The HandPunch® 3000 verifies employees' identities in less than one second, based on the unique size and shape of their hands. HandPunch 3000 clearly notifies each user of a match using red and green indicator lights. Because no one can punch in or out for your employees, the system reduces time theft and improves payroll accuracy.

Versatile and programmable

Beyond a simple time clock, the HandPunch 3000 provides definable data management keys that allow data collection when employees punch. The readers transmit data to the time and attendance host PC through a variety of methods including direct wiring, modem and Ethernet. The HandPunch 3000 also has the ability to control a door. When you want to cut time and attendance costs...do it by hand.



FEATURES & BENEFITS

- Saves money over card-based systems
- Eliminates Badges
- Eliminates Buddy Punching
- Fast and easy to use
- Provides the most accurate time and attendance solution available

Hand Geometry Technology

The HandPunch® 3000 uses Ingersoll Rand Recognition Systems' field-proven hand geometry biometric technology. The terminal captures a three-dimensional image of the hand each time the employee punches. The hand's size and shape are used to verify their identity with unparalleled accuracy. No fingerprints or palm prints are utilized. Green and red lights notify the employee of the status of each punch. There's no question any more; employees have to be there to punch.

Programmable Data Management Keys

The HandPunch 3000 has two user-definable data management keys that let you collect data as employees punch. Common uses include department transfers, tips collected, job codes, or pay codes. Multi-level data entry sequences may be defined. You can also set the data management keys to allow employees to review their past punches. To reduce keystrokes, the keys can also be set to automatically enter data such as a frequently used department number or in/out status.

Communication Options

Whether your application calls for one terminal or thousands, the HandPunch 3000 can meet the need. Multiple terminals can be networked together at a site via RS-485 wiring. An optional Ethernet communications module or dial up modem are also available. Both options are internal to the terminal making installation fast and simple.

Edit-at-the-Clock Functions

The HandPunch 3000 allows supervisors to override user restrictions and to input such items as missed punches, planned vacations, and sick time at the terminal. The password-protected mode provides greater supervisor flexibility by lessening the need for computer edits. Audit trails documenting the use of these functions are generated to ensure security.

Bell Schedules

The bell schedule lets you program the day, time and duration of a series of bells. The bells can be programmed to signal the beginning or end of a shift, lunch or break.

Door Control

The HandPunch 3000 provides the capability to unlock and monitor a door. Global timezones may be used to restrict employee access.

SPECIFICATIONS

Part Number:	HP-3000
Size:	8.85 in (22.3 cm) wide 11.65 in (29.6 cm) high 8.55 in (21.7 cm) deep
Weight:	6 lbs (2.7 kg)
Power:	12 to 24 VDC or 12 to 24 VAC 50-60 Hz, 7 watts
Environment:	Operating: 32°F to 113°F (0°C to 45°C) Relative Humidity: 20% to 80% NC Non-operating (storage): 14°F to 140°F (-10°C to 60°C) Relative Humidity: 5% to 85% NC
Verification Time:	Less than one second
Memory Retention:	Up to 5 years via the standard internal lithium battery.
Transaction Storage:	5120 transactions
ID Number Length:	1 to 10 digits from keypad or card
User Capacity:	512 users expandable to 32,512 users
Template Size:	9 bytes
Communications:	RS-485 (4 and 2 wire) RS-232 Serial Printer Support or network communications
Baud Rate:	300 to 28.8 Kbps
Card Reader Input:	Proximity, Wiegand, Magnetic Stripe, Bar Code (5 VDC provided by HandReader)
Card Reader Output:	Wiegand, Magnetic Stripe, Bar Code
Duress Code:	1 leading digit (user definable)
Door Controls:	Door Lock Output (Sinks 0-24VDC, 100mA max) Door Switch Monitoring Bell Ring Output (Sinks 0-24VDC, 100mA max)
Time Zones:	62 user definable time zones
Options:	BB-200 Operational Battery Backup BC-100 Bar Code Reader Wall Mount DC-102 Data Converter (RS-232 to RS-485) EM-801 Memory Expansion - 9,728 users EM-803 Memory Expansion - 32,512 users EN-200 Ethernet Communications Module MD-500 Internal 14.4 Baud Dial-up Modem WAR-EXT 1 year extended warranty

Recognition Systems

HandPunch® 1000-E

Biometric Time & Attendance Terminal

An Ethernet Biometric time clock that is truly affordable for small to midsize businesses.

Ingersoll Rand Recognition Systems now brings the accuracy and convenience of biometric technology easily within reach of any time and attendance application. In operations that range from the corner deli to franchise chains, Ingersoll Rand Recognition Systems HandReaders have proven themselves to be a practical and precise solution. Our terminals are so affordable, they make card-based systems seem obsolete.



FEATURES & BENEFITS

- Saves money over card-based systems
- Dramatically reduces payroll costs
- Easily integrates into existing network infrastructures
- Eliminates badges
- Eliminates buddy punching
- Fast and easy to use
- Comes standard with an Ethernet card
- Up to 100 users
- Platen also comes standard with a printed hand outline to ensure accurate hand placement while punching

Your Hand Is Your Card

There are no cards to create, administer, carry – or lose. The HandPunch® 1000-E verifies employees' identities in less than one second, based on the unique size and shape of their hands. For small companies, the HandPunch 1000-E provides a quick return on investment by eliminating the cost associated with administrating and managing cards. For companies that have small, multiple locations, minimal supervision leaves opportunity for buddy punching and time fraud. With the HandPunch 1000-E one employee can't punch for the other. Time fraud is eliminated thereby reducing payroll costs and increasing the company's bottom line.

Affordable Ethernet Solution

The HandPunch 1000-E comes standard with a built-in Ethernet connection allowing for quick integration into your time and attendance application and existing network infrastructure.

Hand Geometry Technology

The HandPunch 1000-E uses Ingersoll Rand Recognition Systems' field-proven hand geometry biometric technology. The terminal captures a three-dimensional image of the hand each time the employee punches. The hand's size and the shape are used to verify their identity with unparalleled accuracy. No fingerprints or palm prints are utilized. Green and red lights notify the employee of the status of each punch. There's no question, employees have to be there to punch in.

Small Enterprise Solution

The HandPunch 1000-E provides a new solution for companies with 100 employees or less per terminal or location. Just because you run a small company doesn't mean you don't have time fraud issues. The HandPunch 1000-E terminal allows small companies to put an end to time fraud and begin utilizing biometric technology. The added benefit of standard Ethernet allows easy connectivity to most time and attendance applications. With the HandPunch 1000-E, small companies no longer need to worry about lost timecards, making new cards, or employees clocking in for another employee.



SPECIFICATIONS

Part Number: HP-1000E

Size: 8.85 in (22.3 cm) wide
11.65 in (29.6 cm) high
8.55 in (21.7 cm) deep

Weight: 6 lbs (2.7 kg)

Power: 12 to 24 VDC or 12 to 24 VAC 50-60 Hz,
7 watts

Environment: Operating: 32°F to 113°F (0°C to 45°C)
Relative Humidity: 20% to 80% NC
Non-operating (storage):
14°F to 140°F (-10°C to 60°C)
Relative Humidity: 5% to 85% NC

Verification Time: Less than one second

Memory Retention: Up to 5 years via the standard internal
lithium battery.

Transaction Storage: 5120 transactions

ID Number Length: 1 to 10 digits from keypad

User Capacity: 100 users

Template Size: 9 bytes

Communications: Ethernet 10 Base-T (TCP/IP)

Options: BB-200 Operational Battery Backup
WAR-EXT 1 year extended warranty

HandPunch® is a registered trademark of Ingersoll Rand Recognition Systems
Specifications subject to change. Please check with your system vendor for details.