

Series 2000 (Barcode Terminal) Model t6-2020



Ideal for customers that have already implemented barcode technology timeware® have standardised on barcode type interleaved 2 of 5 for the internal reader

Availability: **In stock**

Compatible with the following software:

timeware®
Small Business Edition

timeware®
Professional Edition

Capacity

1000 employee capacity
3000 archive record capacity

Communication

Flexitime offers intelligent networking: Employees using the system may check their real-time balances at all designated terminals on the WAN/LAN Network connection: RJ45 (10BaseT)
Serial connection: RS232 (9600bps)
Serial modem compatible

Features

Business in/Business out (available late 2003)
Status request (available late 2003)
E-mail messaging
Utilises timeware® SDK: available free to third-party developers

Third-party Software Developers...



What does the SDK do?

The SDK is designed to aid any programmer in creating his/her own application that communicates with a timeware® terminal. Communication to the terminal can be via an RS232 or TCP/IP connection.

Specifications

Terminal dimensions:

Width: 292mm
Length: 178mm
Depth: 76mm
Weight: 700g

Reader type: Champack visible/non-visible barcode reader

Encoding method: Interleaved 2 of 5 (8 digit) code39 Standard secondary TTL barcode reader interface.

Reader size: 90mm

Miscellaneous:

Interfaces with external barcode wand
Standard factory built driver facility

